PCT

(30) Priority data:

9102006-5

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

WO 93/00517 (51) International Patent Classification 5: (11) International Publication Number: A1 F16B 37/06 7 January 1993 (07.01.93) (43) International Publication Date:

(81) Designated States: AT, AU, BB, BG, BR, CA, CH, CS, (21) International Application Number: PCT/SE92/00419 15 June 1992 (15.06.92) (22) International Filing Date:

SE

(71) Applicant (for all designated States except US): AB VOLVO [SE/SE]; S-405 08 Göteborg (SE).

28 June 1991 (28.06.91)

(72) Inventors; and (75) Inventors/Applicants (for US only): STILLBÄCK, Ola [SE/ SE]; Berghöjdsgatan 18, S-422 49 Hisingsbacka (SE). LINDAHL, Lars [SE/SE]; Solvändan 12, S-439 00 Onsala (SE).


(74) Agent: AWAPATENT AB; Box 53252, S-400 16 Göteborg

DE, DK, ES, FI, GB, HU, JP, KP, KR, LK, LU, MG, MN, MW, NL, NO, PL, RO, RU, SD, SE, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LU, MC, NL, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG).

Published

With international search report. In English translation (filed in Swedish).

(54) Title: ELECTRICAL CONTACT NUT



(57) Abstract

The invention concerns an electrical contact nut (1) primarily intended to be welded to a sheet steel component (8) of a motor vehicle, and comprising a first, preferably cylindrical portion (2) and a second, wider portion (3) at one end of the first portion (2). On its side facing the first portion (2), the second portion (3) is provided with an annular member (4) of a weldable material. By means of its first portion (2), the nut (1) may be introduced into an aperture (7) formed in the sheet metal component (8) until the annular welding member (4) abuts against the sheet metal component (8). In this position, the nut may be welded to the component (8).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

ΑT	Austria	FI	Finland	ML	Mali
ΑU	Australia	FR	France	MN	Mongolia
BB	Barbados	GA	Gahon	MR	Mauritania
B€	Belgium	GB	United Kingdom	MW	Malawi
BF	Burkina Faso	GN	Guinea	NL.	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
Bj	Benin	HU	Hungary	PL	Poland
BR	Bravil	Œ	Ireland	RO	Romania
CA	Canada	ίΤ	Italy	RU	Russian Federation
CF	Central African Republic	JР	Japan	SD	Sudan
CG	Сопро	KP	Democratic People's Republic	SE	Sweden
CH	Switzerland		of Korea	SN	Senegal
CI	Côte d'Ivaire	KR	Republic of Korea	รบ	Soviet Union
CM	Camerous	Li	Liechtenstein	TD	Chad
CS	Czechoslovakia	LK	Sri Lanka	TG	Togo
DE	Germony	LU	Luxembourg	us	United States of America
DK	Denmark	MC	Monaco		
ES	Spain	MG	Madaguscar		

PCT/SE92/00419 WO 93/00517

5

20

35

ELECTRICAL CONTACT NUT

The subject invention concerns an electrical contact nut designed to be welded onto a sheet metal component, primarily onto motor vehicle sheet steel components. The nut comprises a first, preferably cylindrical portion and a second portion with larger width dimensions than the 10 first portion.

Electrical contact nuts of this kind are used above all within the automobile industry. The nut is applied in alignment with an aperture formed in the vehicle body, and on the opposite side of the sheet steel a cable socket is 15 attached to the sheet metal in alignment with the aperture, with the aid of a screw-threaded bolt having a head thereon, which bolt is screwed onto the nut. In this manner an earth connection point is provided in the vehicle body.

This prior-art technology suffers from several drawbacks. When the nut is welded to the sheet metal component, care must be taken to ensure that the nut is maintained in an exact position in alignment with the aperture, or else it becomes impossible to screw the bolt 25 into the nut. In addition, it is necessary that the sheet metal side opposite the nut side exhibits a smooth and even surface in order to allow satisfactory earth connection to be established. However, the smoothness of the surface also means that the cable socket mounted at 30 the end of a cable to be secured to the sheet metal component tends to co-rotate with the bolt as the latter is tightened, and consequently some kind of immobilizing force must be exerted on the socket, which complicates the mounting operation.

Should the nut for some reason loosen with respect to the sheet metal and for that reason fall off, for

2

instance in connection with untightening of the connection in order to replace the cable, it may be difficult to weld on a fresh nut, since the latter has to be applied on the side of the sheet metal component that from the

assembler's point of view is the reverse or inner side of the sheet metal component. Another complication is that it may be difficult to dissociate the bolt from the loose nut because of the co-rotation of the latter while at the same time access to the nut is difficult.

With the advent of the electrical contact nut in accordance with the subject invention the drawbacks outlined in the aforegoing are eliminated. The features characterizing the invention are defined in the appended claims.

The invention will be described in closer detail in the following with reference to the accompanying drawing figures, in which:

Fig. 1 is a sectional view through a sheet metal component including an earth connection point embodying 20 the electrical contact nut in accordance with the invention, and

Fig. 2 illustrates the electrical contact nut welded to the sheet metal component in an alternative manner.

The electrical contact nut 1 comprises a first,

25 preferably cylindrical portion 2, and a second, likewise
preferably cylindrical portion 3 which is formed integral
with the first portion 2 but is wider than the latter. On
its side facing the first portion 2, the second portion 3
is provided with an annular member 4 of a weldable

30 material. On its opposite side 5, the second portion 3 is
formed with studs 6, the function of which will be
explained in the following.

The first portion 2 of the electrical contact nut 1 is arranged to be pushed into an aperture 7 formed in a 35 sheet metal component 8, which may be a motor vehicle sheet metal component, sufficiently far for the annular

3

welding member 4 to abut against the sheet metal 8. In this position, the nut 1 is welded firmly to the sheet metal component 8 and once this welding operation is completed, a reliable earth connection has been 5 established.

To mount a cable 9 provided with a cable socket 10, the latter is screwed onto the nut 1 with the aid of a threaded bolt 11 which is threaded into the nut 1, a flange 12 on said nut pressing said cable socket 10 against the studs 6 formed on the front or external side 5 of the nut 1. The studs 6 penetrate into the material of the cable socket 10, preventing the latter from corotating with the bolt 11 when the latter is tightened.

By means of the electrical contact nut in accordance

with the invention the drawbacks referred to in the
aforegoing and found in prior-art electrical contact nuts
are removed. The nut 1 is easily introduced into the
aperture 7, in which it is maintained in position while
being welded to the sheet metal component 8. There is no
need for any position-retaining measures of any kind, in
contrast to what is the case, when the nut 1 is applied
against the sheet metal component 8 on the opposite side
thereof. In addition, and as explained in the aforegoing,
the studs 6 prevent the cable socket 10 from co-rotating
with the bolt 11 when the latter is tightened, a
phenomenon otherwise occurring when the cable socket 10
must be applied against the surface of the sheet metal
component 8, which is painted.

In the event that, for instance as a result of
vibrations in the sheet metal component 8, the nut 1 loses
its grip on the latter, it will not fall off, when the
bolt is loosened but will remain inside the aperture 7,
and in the manner illustrated in Fig. 2 it may be reattached to the component 8 in a simple manner by means of
a fresh welding joint 13.


The electrical contact nut 1 in accordance with the invention is not limited to the embodiment illustrated and described herein but may be varied in many ways within the scope of the appended claims. This applies both to the configuration of the nut 1 itself and to the type of frictional means formed on its outer face 5.


5

CLAIMS

5

- 1. An electrical contact nut intended to be welded to a sheet metal component (8), preferably a sheet metal component of a motor vehicle, and comprising a first, preferably cylindrical portion (2) and a second portion (3) having larger width dimension than the first portion (2), c h a r a c t e r i z e d in that the wider portion (3) of the nut (1) is formed on its side facing the first portion (2), with an annular member (4) of a weldable material, and in that by means of its said first portion (2) the nut (1) may be introduced into an aperture (7) formed in the sheet metal component (8) sufficiently far for said annular welding member (4) to abut against the sheet metal component (8), in which position the nut (1) may be welded to said sheet metal component (8).
- 20 2. An electrical contact nut as claimed in claim 1, c h a r a c t e r i z e d in that on its upper or front side (5), which is the side on the second nut portion (3) that corresponds to the one opposite the annular welding member (4), the nut (1) is provided with means (6) designed to increase the friction against a component, such as a cable socket (10), mounted on said upper or front side (5).
- 3. An electrical contact nut as claimed in claim 2, c h a r a c t e r i z e d in that said means are studs30 (6) projecting from said upper or front side (5).





INTERNATIONAL SEARCH REPORT

International Application No PCT/SE 92/00419

international Application No. PCT/3E 92/00419							
	ON OF SUBJECT MATTER (If several class						
IPC5: F 16 B	ational Patent Classification (IPC) or to both 37/06	National Classification and IPC					
II. FIELDS SEARC	HED						
	Minimum Docum	entation Searched 7					
Classification System							
IPC5	F 16 B						
		er than Minimum Documentation ts are Included in Fields Searched ⁸					
SE,DK,FI,NO	classes as above						
III. DOCUMENTS C	ONSIDERED TO BE RELEVANT						
Category * Cital	tion of Document, ¹¹ with Indication, where ap	propriate, of the relevant passages 12	Relevant to Claim No.13				
17	, 2151324 (DAIMLER-BENZ AK 7 July 1985, see abstract; igures 1-2		1				
Y			2,3				
30	, 2120346 (HAN-CHEN CHANG D November 1983, see page ine 41; figure 1		2,3				
GM Se Se	1, 3102939 (SPRINGFIX BEFE MBH) 2 September 1982, se figures 1-4 se page 7, second part - p art 		1-3				
* Special categories of cited documents: 10 "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or							
"O" document relei other means	"document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "document referring to an oral disclosure, use, exhibition or other means "document referring to an oral disclosure, use, exhibition or other means." "Involve an inventive step document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such document is combined with one or more other such document in the art.						
	priority date claimed	a occument member of the same p	atent tamily				
IV. CERTIFICATION Date of the Actual Completion of the International Search Date of Mailing of this International Search Report							
	26th August 1992 17 -09- 1992						
International Searching	g Authority	Signature of Authorized Officer	<u> </u>				
SWED	Desper Stenström						

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.PCT/SE 92/00419

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on 31/07/92. The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
GB-A- 2151324	85-07-17	DE-C- FR-A-B- JP-C- JP-B- JP-A- US-A-	3345617 2560943 1623968 2047064 60140679 4650274	85-01-10 85-09-13 91-11-18 90-10-18 85-07-25 87-03-17
GB-A- 2120346	83-11-30	NONE		
DE-A1- 3102939	82-09-02	EP-A- JP-A- WO-A-	0071615 57144307 82/02579	83-02-16 82-09-06 82-08-05